


# 1 PRESSED WHEEL

Part No.	Dimension (mm)				Load Rat.(kgf)		Weight Net(g)	Q'ty/ Carton	Remarks
	D	d	B	L	Cr	Cor			
PCA625-7-16L	25.0	6.3	7.4	16.0	34	20	34.54	1,000	
PCA834-9-12L	34.0	8.0	9.0	12.0	25	15	30.54	800	
PCA636-12T-25L	36.0	6.5	12.0	25.0	22	13	35.80	800	
PCA836-9-14L	36.0	8.2	9.0	14.0	25	15	31.54		
PCA836-9-28L	36.0	8.2	9.0	28.0	25	15	47.54		
PCA638-12T-16L	38.0	6.5	12.0	16.0	22	13	33.05	700	
PCA638-12T-18L	38.0	6.5	12.0	18.0	22	13	33.25		
PCA638-12T-25L	38.0	6.5	12.0	25.0	22	13	37.25	700	
PCA638-12T-27L	38.0	6.5	12.0	26.8	22	13	38.05	700	
PCA638-12AL	38.0	6.5	12.0	25.0	11	6			Aluminum Housing
PCA638-12A	38.0	6.6	12.0	18.5	30	17	38.80		One side boss type
PCA640-15T	40.0	6.0	15.0	19.0	22	13	40.98		
PCA640-12T-26L	40.0	6.5	12.0	26.0	22	13	34.29	500	
PCA640-20T-26L	40.0	6.5	20.0	26.0	22	13	44.80	450	
PCA3640-20A	40.0	7.9	20.0	36.0	34	20	77.44		Integral shaft without Bore
PCA840-12A-25L	40.0	8.2	12.0	25.0	34	20	48.14	600	
PCA840-20A-25L	40.0	8.2	20.0	25.0	34	20	56.14	450	
PCA648-16A	48.0	6.5	16.0	24.0	30	17	59.70		
PCA848-16A	48.0	8.2	16.0	24.0	34	20	65.29		
PCA848-16AL	48.0	8.2	16.0	25.0	17	10	41.94		Aluminum Housing
PCA649-16A-24L	49.2	6.5	15.9	24.0	30	17	60.30	250	
PCA650-20T-26L	50.0	6.5	20.0	26.0	34	20	74.04	300	
PCA850-16B	50.0	8.0	16.0	20.0	56	36	85.37		
PCA850-25A	50.0	8.0	25.0	30.0	47	30	101.39		
PCA850-20A	50.0	8.2	20.0	25.0	42	26	77.49		
PCA1050-16A-25L	50.0	10.0	16.0	25.0	47	30	72.12		
PCA1050-16B-20L	50.0	10.0	16.0	20.0	56	36	80.37		
PCA864-20A	64.0	8.0	20.0	25.0	56	36	133.97		
PCA1064-20A	64.0	10.0	20.0	25.0	56	36	122.97		



## FUJI SEISAKUSHO CO. LTD.

Minamisenba No.2 Daiji Bldg.  
 No. 1-10, 3-chome, Minamisemba  
 Chuo-ku, Osaka 542-0081 Japan  
 Phone : 81-6-6243-3771 / Fax : 81-6-6243-6445 / e-mail : info@fuji-bearing.com