







5 PRESSED RADIAL BEARING with FLANGE

Part No.	Dimension (mm)					Type	Load Rat.(kgf)		Weight Net(g)	Q'ty/ Carton	Remarks
	D	D'	d	B	L		Cr	Cor			
PCO20-SK	20.0	22.0	8.0	7.1	8.5	3	31	20	12.29	2,500	
PCO20L-SK	20.0	22.0	8.0	7.1	13.8	3	31	20	14.04	2,500	
PCO22LBR	21.8	24.0	8.2	6.9	10.9	3	27	19	15.92		
PCO23H	22.9	25.4	8.2	8.5	8.8	3	22	14	18.55	1,000	
PCO23HS	22.9	25.4	8.2	8.5	12.7	3	22	14	21.04		
PCO27NN	27.0	30.0	12.2	8.0	14.5	4	40	27	25.52	1,000	
PCR27NS	27.0	30.0	12.2	8.0	14.5	6	39	22	26.17	700	Polyamide Retainer
PCO27F-E	27.2	29.0	10.0	7.5	29.0	4	43	32	25.49		
PCO273SUS	27.3	30.0	12.2	7.3	13.8	3	9	6	24.01		All Stainless Steel
PCM280L	28.0	30.0	10.2	8.0	12.0	2	32	22	28.47	500	
PCO280-B	28.0	30.5	12.0	8.0	10.0	3	43	30	25.16	1,000	
PCO287	28.7	31.8	12.7	9.6	11.4	3	54	38	31.30		
PCO287-RA	28.7	31.8	12.7	9.6	11.4	3	54	38	29.70		Single Seal
PCO30T	30.0	33.2	10.2	9.5	11.2	4	70	49	34.66	500	
PCO30E	30.1	33.2	10.0	9.0	11.0	3	70	50	35.41	500	
PCO32S	31.8	34.1	11.9*	10.5	12.5	3	74	56	42.69		HEX bore
PCO32F-B	32.0	35.0	12.0	10.0	12.0	3	74	56	43.14		
PCO32F	32.0	36.3	12.1	10.0	15.9	3	74	56	47.89		
PCO32E	32.1	35.0	12.0	10.0	13.5	3	74	56	44.35	500	
PCR6201ZZF	34.0	37.0	12.0	11.8	11.8	6	695	310	14.00	500	6201ZZ Bearing inserted
PCA1234M	34.0	37.0	12.1	12.0	17.0	1	125	85	54.96	300	
PCR1234M	34.0	37.0	12.1	12.0	17.0	6	113	66	50.49	300	Polyamide Retainer
PCO34NY	34.1	37.0	12.2	12.0	17.5	4	109	70	52.92	500	
PCO349L	34.9	38.1	15.0	9.5	14.0	3	65	55	53.86	300	d=9/16", 5/8", 3/4" available
PCO349L-2RS	34.9	38.1	15.0	11.9	15.5	3	65	55	59.71	300	Doublbel Seals
PCO351KAI	35.1	38.1	16.0	11.3	12.9	3	93	69	56.87		
PCO1737	37.0	39.0	17.2	12.0	18.5	4	113	87	55.87		
PCO371-NU	37.1	39.0	12.0	12.0	16.5	3	143	90	70.98	500	
PCO371S-HEX	37.1	39.0	11.2*	12.0	17.5	3	133	84	72.27	500	HEX bore
PCM381	38.1	39.5	10.2	12.0	17.0	2	44	31	48.51	500	
PCM382A	38.2	40.2	6.6	12.7	19.1	2	38	21	55.75	350	
PCO40	40.0	44.5	17.0	13.0	15.0	3	137	104	82.85	400	
PCO40L	40.2	44.5	17.0	13.0	18.0	3	137	104	83.85	300	
PCO47R	47.0	51.0	20.0	13.5	16.5	3	179	145	125.17	300	Single Seal
PCA47FM	47.0	51.8	20.0	13.5	16.5	1	180	154	115.57	250	
PCO47F	47.0	51.8	20.0	13.5	16.5	3	159	137	113.67	300	
PCA2047S	47.0	51.8	20.0	13.5	16.5	1	113	77	107.24	200	with Retainer
PCA2547F	47.0	51.8	25.8	14.0	17.0	1	172	166	104.46	200	
PCM476SKAI	47.3	50.8	11.2*	13.5	20.6	2	197	139	136.38		HEX bore
PCM508D-1"	50.8	54.0	25.4	12.7	15.9	2	158	143	132.71	100	d=3/4" available
PCM508-1"	50.8	55.6	25.4	12.7	15.9	2	158	143	132.71		d=3/4" available
PCO52E	52.0	55.2	25.0	15.0	18.0	3	216	180	142.49	200	

* shows dimension of the opposite side



FUJI SEISAKUSHO CO. LTD.

Minamisenba No.2 Daiji Bldg.
 No. 1-10, 3-chome, Minamisenba
 Chuo-ku, Osaka 542-0081 Japan
 Phone : 81-6-6243-3771 / Fax : 81-6-6243-6445 / e-mail : info@fuji-bearing.com