

Printing date 26.06.2003 Reviewed on 26.06.2003

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: ISOFLEX TOPAS NB 52

· Article number: 004131

· Application of the substance / the preparation Grease

· Manufacturer/Supplier:

KLÜBER LUBRICATION MÜNCHEN KG

Geisenhausenerstrasse 7 D-81379 München Tel.: 0049 (0) 897876-0 Fax: 0049 (0) 897876-333

Notfallauskunft: 0049 (0) 897876-700

· Further information obtainable from: Material Compliance Management

2 Composition/information on ingredients

- · Chemical characterization
- · Description:

Synthetic hydrocarbon oil barium complex soap

· Dangerous components:

barium complex soap

R 52/53 25-50%

· Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- · Hazard description: Not applicable.
- · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- \cdot After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Wash off with soap and plenty of water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

GB

(Contd. on page 2)

Printing date 26.06.2003 Reviewed on 26.06.2003

Trade name: ISOFLEX TOPAS NB 52

(Contd. of page 1)

5 Fire-fighting measures

· Suitable extinguishing agents:

Water haze

Foam

Fire-extinguishing powder

Carbon dioxide

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Standard procedure for chemical fires.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

6 Accidental release measures

- · Person-related safety precautions: Not required.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Pick up mechanically.

Dispose of the material collected according to regulations.

7 Handling and storage

- · Handling:
- \cdot Information for safe handling: No special measures required.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- \cdot Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions: None.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- \cdot Ingredients with limit values that require monitoring at the work place:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Avoid close or long term contact with the skin.

Be sure to clean skin thoroughly after work and before breaks.

- · Respiratory protection: Not required.
- Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended.
- · Eye protection: Not required.

GB

Printing date 26.06.2003 Reviewed on 26.06.2003

Trade name: ISOFLEX TOPAS NB 52

(Contd. of page 2)

· General Information		
Form: Colour: Odour:	Pasty Beige Product specific	
· Change in condition Drip point:	> 240°C (DIN ISO 2176)	
· Flash point:	-°C	
· Danger of explosion:	Product does not present an explosion hazard.	
· Density at 20°C:	0.96 g/cm³	
· Solubility in / Miscibility water:	with Insoluble.	

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Materials to be avoided: oxidizing agents
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: none under normal use

11 Toxicological information

· Additional toxicological information:

Prolonged skin contact may cause skin irritation and/or dermatitis.

12 Ecological information

- · Ecotoxical effects:
- \cdot **Behaviour in sewage processing plants:** The product can be mechanically separated.
- · General notes:

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation Can be incinerated in accordance with local and national regulations.
- · Waste disposal key:

For this product no waste disposal key according the European Waste Catalogue (EWC) can be determined, as only the purpose of application defined by the user enables an allocation. The waste code number has to be determined in accordance with the local waste disposer.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

GB

Printing date 26.06.2003 Reviewed on 26.06.2003

Trade name: ISOFLEX TOPAS NB 52

(Contd. of page 3)

14 Transport information

- · Land transport ADR/RID (cross-border)
- · ADR/RID class:
- · Maritime transport IMDG:
- · IMDG Class:
- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -
- · Transport/Additional information: Not classified as dangerous according to the above specifications.

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Risk phrases:

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- · Department issuing MSDS: Material Compliance Management
- · Contact: Tel.: +49 (0) 897876-564

CD