

ISOFLEX® SUPER LDS 18

Dynamically light grease for plain and rolling bearings



Description:

ISOFLEX SUPER LDS 18 is a low-noise, high speed grease for plain and rolling bearings. It consists of ester oil, mineral oil and lithium soap. It protects against corrosion and is resistant to ageing and oxidation.

Application:

ISOFLEX SUPER LDS 18 is suitable for plain and rolling bearings, small and miniature bearings, low-noise and precision bearings, for precision mechanical and optical equipment and low-temperature applications.

It can also be used as an anti-corrosion and anti-wear lubricant in electrical contacts, where it reduces electric resistance in the contact surface. Properly applied, ISOFLEX SUPER LDS 18 increases electric conductivity in the low-voltage range, protects against corrosion and oxidation, improves sliding properties and reduces wear, e.g. in sliding contacts and potentiometers.

Application notes:

The lubricant is applied by brush, spatula, or grease gun. Owing to the different compositions of elastomers and plastic materials, compatibility tests are indispensable before series application.

Minimum shelf life:

The minimum shelf life is approx. 36 months if the product is stored in the original closed container in a dry place.

Pack sizes:

45 g PE tubes
400 g cartridges
1 kg cans
25 kg buckets

ISOFLEX SUPER LDS 18

- Low-noise and low-friction grease
- Good corrosion protection
- Resistant to oxidation and ageing
- Low specific electrical resistance

Product data:

Colour	yellow
Texture	homogeneous, short-fibred
Service temperature range*, °C, approx.	– 50 to 120
Drop point, DIN ISO 2176, °C	> 190
Density, at 20 °C, g/cm ³ , approx.	0.90
Worked penetration, DIN ISO 2137, (ASTM D 217); 0.1 mm	265 to 295
Copper corrosion, DIN 51 811 (lubricating grease), 24 h / 120 °C, corrosion rating	1 – 120
Base oil viscosity, DIN 51 562/1, at 40 °C, mm ² /s, approx. at 100 °C, mm ² /s, approx.	15 4
Speed factor** (n x d _m), mm x min ⁻¹ , approx.	1,000,000
Apparent dynamic viscosity, Klüber viscosity grade***	L
Specific electrical resistance, Ω x cm 25 °C, approx.	5 x 10 ⁹

* Service temperatures are guide values which depend on the lubricant's composition, the intended use and the application method. Lubricants change their consistency, apparent dynamic viscosity or viscosity depending on the mechanical loads, time, pressure and temperature. These changes in product characteristics may affect the function of a component.

** Speed factors are guide values which depend on the type and size of the rolling bearing type and the local operating conditions, which is why they have to be confirmed in tests carried out by the user in each individual case.

*** Klüber viscosity grades: EL = extra light lubricating grease; L = light lubricating grease; M = medium lubricating grease; S = heavy lubricating grease; ES = extra heavy lubricating grease

ISOFLEX® SUPER LDS 18

Safety Data Sheet

<p>1.1 Product name: ISOFLEX SUPER LDS 18 Code-No.: 004 024 08.03.2000</p>
<p>1.2 Klüber Lubrication München KG Emergency telephone no.: Geisenhausenerstraße 7 ++49 - 89 7876 - 0 D-81379 München Tel. ++49 - 89 78 76 - 0 telephone exchange Fax: ++49 - 89 78 76 - 333</p>
<p>2. Composition / information on ingredients Chemical characterization (preparation): Ester oil, mineral oil, lithium soap</p>
<p>3. Hazards identification No particular hazards known</p>
<p>4. First aid measures After inhalation: Not applicable After contact with skin: Wash off with soap and plenty of water After contact with eyes: Rinse with plenty of water After ingestion: Do not induce vomiting. Obtain medical attention Advice to doctor: Treat symptomatically</p>
<p>5. Fire-fighting measures Suitable extinguishing media: Water spray, foam, dry powder, carbon dioxide (CO₂) Unsuitable extinguishing media: High volume water jet Special Hazards: In case of fire the following can be released: Carbon monoxide, hydrocarbons Special protective equipment for firefighters: Standard procedure for chemical fires Additional information: Water mist may be used to cool closed containers. In the event of fire and/or explosion do not breathe fumes</p>
<p>6. Accidental release measures Personal precautions: Not required Environmental precautions: Do not flush into surface water or sanitary sewer system Methods for cleaning up / taking up: Use mechanical handling equipment. Dispose of absorbed material in accordance with the regulations Additional information: None</p>
<p>7. Handling and storage Advice on safe handling: No special handling advice required Advice on protection against fire and explosion: No special precautions required Requirements on storage rooms and vessels: No special storage conditions required Incompatible materials: Incompatible with oxidizing agents. Do not store together with food Further information on storage conditions: Store at room temperature in the original container</p>
<p>8. Exposure controls / personal protection Additional advice on system design: Not applicable Ingredients and specific control parameters: None Respiratory protection: No special protective equipment required Hand protection: No special protective equipment required Eye protection: No special protective equipment required Body protection: No special protective equipment required Other protection measures: No special protective equipment required General protection and hygiene measures: Avoid prolonged and/or repeated contact with skin. Remove soiled or soaked clothing immediately. Clean skin thoroughly after work; apply skin cream</p>

<p>9. Physical and chemical properties Form: paste Colour: yellow Odour: characteristic Drop point: > 190 °C, DIN ISO 2176 Flash point: > 200 °C (base oil) Flammability: not applicable Ignition temperature: not applicable Autoflammability: not applicable Lower explosion limit: not applicable Upper explosion limit: not applicable Vapour pressure-first: not applicable Density: approx. 0.90 g/cm³, 20 °C Water solubility: insoluble pH value: not applicable Kinematic viscosity: not applicable Further information: none</p>
<p>10. Stability and reactivity Conditions to avoid: None Materials to avoid: Strong oxidizing agents Hazardous decomposition products: None under normal use Additional information: None</p>
<p>11. Toxicological information The toxicological data has been taken from products of similar composition Acute toxicity: LD₅₀/oral/rat = > 2 g/kg (literature data) Chronic toxicity: None Human experience: Prolonged skin contact may cause skin irritation and/or dermatitis</p>
<p>12. Ecological information Information on elimination (persistence and degradability): Product is insoluble in water. May be separated out mechanically in purification plants Behaviour in environmental compartments: Ecological injuries are not known or expected under normal use Ecotoxic effects: Aquatic toxicity is unlikely due to low solubility Additional information: Should not be released into the environment</p>
<p>13. Advice on Disposal Disposal: Can be incinerated when in compliance with local, state and federal regulations Dispose of contaminated packaging and recommended cleaning: Offer rinsed packaging material to local recycling facilities</p>
<p>14. Transport information GGVS / GGVE: not applicable ADN / ADNR: not applicable IMDG-Code: not applicable ICAO / IATA-DGR: not applicable Further information: Not classified as dangerous in the meaning of transport regulations</p>
<p>15. Regulatory information Labelling according to EU-guidelines: The product does not require a hazard warning label in accordance with EC-directives/German regulations on dangerous substances National regulations</p>
<p>16. Other information Issue-department of Safety Data Sheet: Chemical Documentation, Tel.: ++49 - 89 7876 - 564</p>

The data in this product information is based on our general experience and knowledge at the time of printing and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. We recommend contacting our Technical Consulting Staff to discuss your specific application. If required and possible we will be pleased to provide a sample for testing. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this product information at any time without notice.



Klüber Lubrication München KG, a member of the Freudenberg group