

FAG Rolling Bearing Grease Arcanol TEMP200

Properties, applications: High temperature grease for high loads

Characteristics	Unit	Value	Test method
Marking:		KFK2U-40	DIN 51825
Colour:		white	
Temperature range:	[°C]	-40 to 260	DIN 51825
Longtime limit temperature:	[°C]	200	
Density	[kg/dm ³]	1,96	
Specifications:			
Thickener:		PTFE	
Type of base oil:		fluorinated polyether oil	
Base oil viscosity	at 40°C: [mm ² /s]	400	DIN 51562 - 1
	at 100°C: [mm ² /s]	35	DIN 51562 - 1
Identification letters of additives:			
Worked penetration:	[0,1 mm]	265-295	DIN ISO 2137
Consistency:	[NLGI-Cl.]	2	DIN 51818
Drop point:	[°C]	not measurable	DIN ISO 2176
Oxidation stability			
Pressure drop after 100 h at 99	[kPa]	< 80	DIN 51808
Water resistance:	[Range]	0-90	DIN 51807 - 1
Flow pressure at -30 °C	[hPa]	< 1400	DIN 51805
Emcor Test:	[Corr.Grad]	0/1	DIN 51802
Copper corrosion after 24 h/100 °C	[Corr.Grad]	1	DIN 51811
Four ball weld load:	[N]	4500	DIN 51350 - 4
Wear scar of four ball test:	[mm]		DIN 51350 - 5
FE8 tests (rolling element wear)			
536050 - 7,5/ 80 - 150	v10 / v50 [mg]	7 / 19	DIN 51819
FE9 tests (grease service lifetime)			
A / 1500 / 3000 - 150	F10/F50 [h]	1000 /	DIN 51821
A / 1500 / 3000 - 260	F10/F50 [h]	132 / 158	DIN 51821
Speed range:	Unit	Ball bearings and cylindrical roller bearings	Other roller bearings*)
Speed limit n*dm	[mm/min]	300.000	100.000

*) not cylindrical roller thrust bearings and spherical roller thrust bearings

This copy is not taken into account by the updating service.

The data are based on actual knowledge at the time of print and refer to the respective test method. Guaranteed properties or warranties cannot be taken over.

1. Identification of substance/preparation and company

Identification of the substance or preparation
Product name: FAG Arcanol TEMP200*)
Company/undertaking identification
Supplier:
FAG Kugelfischer AG
Postfach 1260
D-97419 Schweinfurt
Contact numbers: Tribology/Chemistry
Tel. 09721/91-4681
Fax 09721/91-1766
Emergency number: Tel. 09721/91-0

2. Composition/information on ingredients

Composition
Description:
Rolling bearing grease containing PTFE (thickener) and fluorinated polyether (base oil).
Dangerous components:
CAS-Nr./Name, Content, Label, R-Phrases
None

3. Hazards identification

Prolonged or repeated exposure may give rise to dermatitis. Avoid spillage. Weakly water endangering. Not readily biodegradable. If heated above 260 °C or even higher temperatures (eg disassembly of rolling bearings with welding burner) gases and vapours may be produced hazardous to health.

4. First-aid measures

Other information
Advice to physicians: Treat symptomatically.
After inhalation
Inhalation of any vapours from this product is not likely and does not present an acute hazard. Remove to fresh air. Seek medical advice.
After contact with skin
Remove contaminated clothing and wash affected skin with water and soap. If high pressure injection injuries occur, obtain medical attention immediately; surgery is urgently needed.
After contact with eye
Rinse immediately with plenty of water for several minutes and seek medical advice.
After ingestion
Do not induce vomiting. Oil compounds could get into lungs. Obtain medical attention.

5. Fire-fighting measures

Suitable extinguishing media
Product itself is unburnable. Take fire fighting measures appropriate to the environment. Cool closed container with water mist.
Extinguishing media which must not be used for safety reasons
Not applicable.
Special hazards arising from the product itself, combustion products, gases
Combustion is likely to give fluorinated compounds.
Special protective equipment for fire-fighters
Protection clothes and respiratory protection if ventilation is poor.

6. Accidental release measures

Personal precautions
Prevent skin and eye contact. Serious danger of skidding after spillage.
Environmental precautions
Prevent further leakage or spillage. Prevent from entering into drains, ditches or rivers by using appropriate barriers. After entering into surface water, drains or underground inform the appropriate authorities.
Methods for cleaning up
Shovel into a suitable, clearly marked container for disposal in accordance with local regulations.

7. Handling and Storage

Handling
When using do not eat or drink. When handling product in heavy containers safety footwear should be worn and proper handling equipment should be used. Prevent spillages or oil mist.
Notice for fire and explosion protection: None.
Storage
Warehouse and containers: Comply with local regulations for storage of water endangering products. Do not store together with foodstuff. Recommended storing temperature: room temperature.

8. Exposure controls/personal protection

Informations on engineering measures
Keep national regulations concerning water endangering products.
Occupational exposures to be controlled
None. Avoid oil mist.
Personal protection
Respiratory protection:
Not normally required. Use suction plant in case of oil mist.
Hand protection:
Neoprene, PVC or nitril rubber gloves if splashes are likely to occur and if applicable. Otherwise use cream against skin irritations.
Eye protection:
Safety spectacles if splashes are likely to occur.
Skin protection:
Minimise all forms of skin contact. Recommendation: Wear overalls.
Hygiene measures:
Avoid prolonged and repeated contact with skin. Remove contaminated clothes. Skin protection during work and skin care after work. Don't keep oily rags in your pockets. Keep away from foodstuff, beverages and animal food. When using do not eat, drink, smoke and do not take snuff.

9. Physical and chemical properties

Appearance
Semi-solid, colour whitish, without odour.
Safety relevant data
Dropping point (DIN ISO 2176) not measurable
Flashpoint (DIN ISO 2592) without flashpoint
Density (20 °C) approx. 1960 kg/m³
Solubility in water (20 °C) almost insoluble

10. Stability and reactivity

Conditions to avoid

Stable under normal use conditions.

Materials to avoid

Reactions with strong alkalines or other bases. Reactions with alkali metals and alkaline earth metals. Reactions with strong Lewis acids like $AlCl_3$, SbF_5 or CoF_3 .

Hazardous decomposition products

Above approximately 260 °C formation of small amounts of fluorinated compounds possible. Increasing amounts with rising temperature.

Other information

Friction with some metals (eg titanium, aluminium and its alloys) under boundary conditions may result in small amounts of fluorinated decomposition products already at temperatures above 170 °C.

11. Toxicological information

Toxicological data

LD₅₀ oral (rat): > 2000 mg/kg (literature, similar products).

Known human effects

No special effects known.

Other information

Expected to be slightly skin irritant after repeated exposition. Not expected to be a skin sensitiser. Prolonged or repeated contact may cause defatting of the skin which can lead to dermatitis and may make the skin more susceptible to irritation and penetration by other materials.

Toxicological information given is based on a knowledge of the toxicology of similar products and of toxicology of components.

12. Ecological information

Degradability and accumulation

Product is not readily biodegradable.

Mobility

Product is not soluble in water. It may be removed mechanically from sewage plants.

Ecotoxicity

No data available. Product is removable nearly entirely from sewage plants mechanically. Nevertheless prevent from spreading or entering into drains, ditches or rivers.

Other information

Avoid spillage.

13. Disposal considerations

Product

Must not be disposed of together with household garbage. Recommendation: Dispose to licensed disposal contractor (recycling or incineration). Contains halogene. European waste catalog, EWC-Code: 120112 Used waxes and greases.

Contaminated packaging

Recommendation: Drain container thoroughly. Dispose to licensed disposal contractor. Cleaning by disposal contractor for recycling.

14. Transport information

Not dangerous for conveyance.

Land transport ADR/RID and GGVS/GGVE: Not dangerous.

Inland water transport ADN/ADNR: Not dangerous.

Sea transport IMDG/GGVSee: Not dangerous.

Air transport ICAO-TI and IATA-DGR: Not dangerous.

15. Regulatory information

EC classification

Not classified as dangerous.

National regulations

Germany: Gefahrstoffverordnung: Not classified as dangerous.

Störfallverordnung: Not listed in enclosure II.

VbF: Not classified.

TA-Luft: Organic compounds, class III, not applicable.

Water endangering group: WGK 1 weakly water endangering (self-classification).

16. Other information

This information is based on our current knowledge of test results, comparison with similar products and information from subdeliverer. Technical data are health, safety and environmental information only. They are no technical product information.

Additional information:

Concawe report 5/87 Health Aspects of Lubricants, german translation DGMK-Bericht 400-7, source of supply Deutsche Gesellschaft für Erdöl, Erdgas und Kohle e. V., Steinstrasse 7, D-20095 Hamburg, Tel. 0049-40-326468.