



Series	Type	Internal Construction	Size Specification	Seal	Mounting Method	O.D. Configuration	
Camrol Bearings							
CF	Standard Stud	Full Complement Needle Rollers	Roller Diameter in Inches	Unsealed	Screwdriver Slot	Cylindrical	
CF-S				Lubri-Disc		Crowned	
CCF-S				Hex Hole	Unsealed	Cylindrical	
CF-B					Lubri-Disc	Crowned	
CF-SB					Unsealed	Cylindrical	
CCF-SB	Lubri-Disc			Crowned			
CFE-B	Eccentric Stud			Unsealed	Screwdriver Slot	Cylindrical	
CFE-SB				Lubri-Disc		Crowned	
CCFE-SB				Unsealed	Cylindrical		
CFH	Heavy Stud			Unsealed	Screwdriver Slot	Cylindrical	
CFH-S		Lubri-Disc	Crowned				
CCFH-S		Hex Hole	Unsealed	Cylindrical			
CFH-B			Lubri-Disc	Crowned			
CFH-SB			Unsealed	Cylindrical			
CCFH-SB	Lubri-Disc	Crowned					
CYR	Yoke	Unsealed	Yoke	Cylindrical			
CYR-S		Lubri-Disc		Crowned			
CCYR-S		Unsealed	Cylindrical				
Bushing Camrol Bearings							
BCF-S	Standard Stud	Bushing	Roller Diameter in Inches	Lubri-Disc	Screwdriver Slot	Cylindrical	
BCF-SB					Hex Hole	Crowned	
BCCF-SB					Yoke	Cylindrical	
BCYR-S	Crowned						
CRES Camrol Bearings							
CF-SB CR	Standard Stud	Full Complement Needle Rollers	Roller Diameter in Inches	Lubri-Disc or Lubri-Disc +	Hex Hole	Cylindrical	
CFE-SB CR	Eccentric Stud						
CYR-S CR	Yoke				Yoke		
Heavy-Duty Camrol Bearings							
CFD	Standard Stud	Double Row Cylindrical Rollers	Roller Diameter in Inches	Rubber Lip	Hex Hole	Cylindrical	
CCFD						Crowned	
CYRD	Yoke				Yoke	Cylindrical	
CCYRD					Crowned		
Special-Duty Camrol Bearings							
SDCF	Standard Stud	Caged Needle Rollers	Roller Diameter in Inches	End Plug and Lubri-Disc +	Hex Hole	Cylindrical	
Metric Camrol Bearings							
MCF	Standard Stud	Full Complement Needle Rollers	Roller Diameter in Millimeters	Lubri-Disc	Screwdriver Slot	Crowned	
MCF-S						Unsealed	Cylindrical
MCF-SX						Lubri-Disc	Crowned
MCFR		Caged Needle Rollers				Cylindrical	
MCFR-S						Crowned	
MCFR-SX		Full Complement Needle Rollers			Cylindrical		
MCF-SB		Eccentric Stud			Caged Needle Rollers	Crowned	
MCF-SBX					Full Complement Needle Rollers	Cylindrical	
MCFR-SB					Caged Needle Rollers	Crowned	
MCFR-SBX		Full Complement Needle Rollers			Cylindrical		
MCFE-SB	Eccentric Stud	Full Complement Needle Rollers	Crowned				
MCFRE-SB		Caged Needle Rollers					
MCYR	Yoke	Full Complement Needle Rollers	Bore Diameter in Millimeters	Lubri-Disc	Yoke	Crowned	
MCYR-S						Unsealed	Cylindrical
MCYR-SX						Lubri-Disc	Crowned
MCYRR		Caged Needle Rollers			Unsealed	Crowned	
MCYRR-S					Lubri-Disc	Cylindrical	
MCYRR-SX					Crowned		
Metric Heavy-Duty Camrol Bearings							
MCFD	Standard Stud	Double Row Cylindrical Rollers	Roller Diameter in Millimeters	Metal Shield	Screwdriver Slot	Crowned	
MCFD-X						Cylindrical	
MCYRD	Yoke		Bore Diameter in Millimeters		Crowned		
MCYRD-X			Cylindrical				
Metric Special-Duty Camrol Bearings							
SDMCF	Standard Stud	Caged Needle Rollers	Roller Diameter in Millimeters	End Plug and Lubri-Disc +	Hex Hole	Cylindrical	
Trakrol Bearings							
PCF	Standard Stud	Ball or Tapered Roller Bearings	Roller Diameter in Inches	Rubber Lip and End Plug	Hex Hole	Cylindrical	
PCFE	Eccentric Stud					Flanged	
FCF	Standard Stud					Flanged	
FCFE	Eccentric Stud		Point Diameter in Inches		V-Grove		
VCF	Standard Stud				Cylindrical		
VCFE	Eccentric Stud	Flanged					
PCYR	Yoke	Tapered Roller Bearings	Roller Diameter in Inches	Rubber Lip	Yoke	Cylindrical	
FCYR			Point Diameter in Inches			Flanged	
VCYR			V-Grove				

APPLICATION CONSIDERATIONS

The proper selection and application of power transmission products and components, including the related area of product safety, is the responsibility of the customer. Operating and performance requirements and potential associated issues will vary appreciably depending upon the use and application of such products and components. The scope of the technical and application information included in this publication is necessarily limited. Unusual operating environments and conditions, lubrication requirements, loading supports, and other factors can materially affect the application and operating results of the products and components and the customer should carefully review its requirements. Any technical advice or review furnished by Emerson Power Transmission Corporation and its divisions with respect to the use of products and components is given in good faith and without charge, and Emerson assumes no obligation or liability for the advice given, or results obtained, all such advice and review being given and accepted at customer's risk. For a copy of our Standard Terms and Conditions of Sale, Disclaimers of Warranty, Limitation of Liability and Remedy, please contact Emerson Power Transmission customer service, 1-800-626-2120. These terms and conditions of sale, disclaimers and limitations of liability apply to any person who may buy, acquire or use an Emerson Power Transmission Corporation product referred to herein, including any person who buys from a licensed distributor of these branded products.

The trademarks MCGILL, CAMROL, CAGEROL, MIR, GUIDEROL, LUBRI-DISC, SPHERE-ROL, NYLAPLATE, LAMBDA, TRAKROL, MCFD, MCYRD, MCF, MCFR, MCFR and MCYRR are registered trademarks of Emerson Power Transmission Manufacturing, L.P. and/or McGill Manufacturing Co., Inc. Emerson Power Transmission and McGill Manufacturing are not responsible for printing errors as they may appear in this publication. Bearing specifications subject to change between reprint issues. The Emerson logo is a trademark and a service mark of Emerson Electric Co. © 2007, 2008 Emerson Power Transmission Manufacturing, L.P. or affiliates. All rights reserved.