


Bearing and Seal Features Selection Chart




Bearing Type	Eccentric Locking Collar	Set Screw	Grip-It	Flush IR	Extended IR	Cylindrical OD	Spherical OD	Relube	Non-Relube	Snap Ring	Anti-Rotation Pin	Standard Seals (See below)	Optional Seals/Shields (See below)
FH	•		•			•		•				1	5
FH-G	•		•			•	•					1	5
FHR	•		•		•			•				1	5
HC	•			•		•	•					2	1, 3, 4, 5, 6
HCR	•			•	•			•				2	1, 3, 4, 5, 6
*HCX	•			•		•	•					2	1, 3, 4, 5, 6
*HER	•			•	•		•		•			2	1, 3, 4, 5, 6
FHL	•		•			•		•				1	5
FHRL	•		•		•			•				1	5
FHS		•	•			•		•				1	5
FHS-G		•	•			•	•					1	5
FHSR		•	•		•			•				1	5
SER		•		•	•		•		•			2	1, 3, 4, 5, 6
UC		•		•		•	•			•		2	1, 3, 4, 5, 6
UCR		•		•	•			•				2	1, 3, 4, 5, 6
UCX		•		•		•	•			•		2	1, 3, 4, 5, 6
GR			•	•		•	•			•		2	1, 3, 4, 5, 6
GER			•	•	•		•		•			2	1, 3, 4, 5, 6


Standard Mounted Units




1
RST-Seal
Full cover metal shroud with Buna-N rubber lip.




2
R-Seal
Full cover metal shroud with Buna-N rubber lip plus slinger.




3
TRL-Seal
Full cover metal shroud with triple (3) Buna-N rubber lips.



4
DBL-Seal
Full cover metal shroud with double (2) Buna-N rubber lips.



5
Z-Shield
Full cover metal shroud.



6
Z-Shield/Slinger
Full cover metal shroud with slinger.

* Not in catalog but available.