

Vierpunktlager / four-point bearings

Abmessung dimensions mm					Tragzahl load rating kN		Drehzahlgrenze speed limit min ⁻¹		Kurzzeichen code	Gewicht weight	Preis gross price
d	D	B	r _s min	a ~	dyn. C	stat. C ₀	grease	oil	bearing	kg	EUR
30	62	16	1,0	32,0	36,50	27,50	9000	13000	QJ206MPA	0,240	79,92
30	72	19	1,1	36,0	58,50	43,00	8000	11000	QJ306MPA	0,420	87,57
30	72	19	1,1	36,0	58,50	43,00	8000	11000	QJ306TVP	0,372	65,78
30	72	19	1,1	36,0	42,40	37,00	6000	8100	Q306MAS	0,420	92,56
30	72	19	1,1	36,0	42,40	37,00	6000	8100	Q306MPA	0,420	87,57
30	72	19	1,1	36,0	42,40	37,00	6000	8100	Q306TVP	0,372	65,78
35	72	17	1,1	38,0	44,00	35,50	8000	11000	QJ207MPA	0,347	88,33
40	80	18	1,1	42,0	54,00	45,50	7000	9500	QJ208MPA	0,400	84,73
40	80	18	1,1	42,0	54,00	45,50	7000	9500	QJ208TVP	0,388	65,85
40	90	23	1,5	46,0	86,50	68,00	6300	8500	QJ308MPA	0,700	118,89
40	90	23	1,5	46,0	86,50	68,00	6300	8500	QJ308TVP	0,689	83,29
45	85	19	1,1	45,0	64,00	57,00	6300	8500	QJ209MPA	0,500	91,14
45	85	19	1,1	45,0	64,00	57,00	6300	8500	QJ209TVP	0,482	69,14
50	90	20	1,1	49,0	61,00	56,00	6000	8000	QJ210MPA	0,575	143,15
60	110	22	1,5	60,0	91,50	93,00	4800	6300	QJ212MPA	0,925	166,60
60	110	22	1,5	60,0	91,50	93,00	4800	6300	QJ212TVP	0,869	101,80
65	140	33	2,1	72,0	136,00	139,00	2800	3800	Q313MB	2,690	307,56
75	130	25	1,5	72,0	125,00	129,00	4000	5300	QJ215N2MPA	1,470	274,76
85	180	41	3,0	93,0	195,00	226,00	2200	2900	Q317MB	5,490	577,37
90	160	30	2,0	88,0	176,00	186,00	3200	4300	QJ218N2MPA	2,800	442,55