Double row track rollers - *with gothic groove*





Cages and shields

- **Available**
- **Feasible** (minimum quantity)
- **Out of program**

d	D	B	C	D1	Dw	r_s min	Designation	Limiting speeds rpm x 1'000 Oil	Grease	Contact seals	Basic load ratings Dyn. Cr kN	Stat. Cor kN	Balls	Abutment dimensions da min mm / inch	Mass ~ gr	Designation	Cage T9H Shields Open	Z	2Z	RSR	2RSR	RSF	2RSF	RSV	2RSV
			mm / inch																						
5	17	8	7	27	6	0.2	**LFR50/5**	45	38	24	2.02	0.93	14x3/32"	6.4	10	**LFR50/5**	■	■	■	■	■	■	■	■	■
.197	.669	.315	.276	1.063	.236	.008								.252											
8	24	11	11	34	6	0.3	**LFR50/8**	36	30	20	5.07	2.58	14x5/32"	10.0	30	**LFR50/8**	■	■	■	■	■	■	■	■	■
.315	.945	.433	.433	1.339	.236	.012								.394											
12	35	15.9	15.9	51.3	10	0.6	**LFR5201**	30	24	15	10.70	5.87	14x6mm	14.0	80	**LFR5201**	■	■	■	■	■	■	■	■	■
.472	1.378	.626	.626	2.020	.394	.024								.551											
	35	15.9	15.9	55.5	12	0.6	**LFR52012**	30	24	15	10.70	5.87	14x6mm	14.0	80	**LFR52012**	■	■	■	■	■	■	■	■	■
	1.378	.626	.626	2.185	.472	.024								.551											

Copyright by WIB 2000